

SERENIX PROFESSIONAL AUDIO

SR-OFD-106PW

Bluetooth active wall pair — 2 × 20 W with 75 W handling and 150° conical coverage.

A Bluetooth active wall-mounted speaker system of one powered main cabinet and one passive satellite. Two channels of Class-D amplification drive a two-way 5-inch and 1-inch system with 75 watts of handling. Clear sound and wide conical coverage suit meeting rooms and multimedia rooms; white and black finishes and an adjustable bracket are supplied.

20 W × 2	75 W	90 dB	108 dB	150°
@ 8 Ω	POWER HANDLING	SPL	PEAK SPL	CONICAL



FEATURES

- 01

Active plus passive

The main cabinet carries the amplification and feeds the satellite over a Phoenix connector.
- 02

Split power handling

75 W total; 50 W across LF and mid range, 25 W at HF.
- 03

Bluetooth and analogue

Bluetooth receiver with unbalanced RCA inputs and a 6.35 mm microphone jack.
- 04

Wide conical coverage


150° coverage from a compact wall cabinet suits square meeting rooms.

SPECIFICATIONS

Rated power	20 W × 2 @ 8 Ω
Power handling	75 W (LF / mid 50 W, HF 25 W)
Speaker units	Woofer 5" + tweeter 1"
Amplifier	2-channel digital stereo, Class D
Audio inputs	Balanced L&R via Phoenix; unbalanced L&R via RCA
Material	ABS enclosure, metal bracket and grille
Finish	White and black available
Frequency response	40 Hz–50 kHz at 1 W, ±3 dB
THD	<0.05 % at 1 kHz, 1/3 rated power
S / N	>70 dB
SPL	90 dB; 108 dB peak
Dispersion	150° conical
Protection	Over-temperature, overload
Power	AC 110 V; AC 220–240 V, 50–60 Hz
Dimensions	170 × 185 × 250 mm
Mounting	Adjustable U-shaped bracket
Net weight	4.8 kg (pair)


The source specification table for this model is headed SR-OFD-230PW-B. All figures are nominal, per manufacturer data.

FREQUENCY RANGE



Published upper limit of 50 kHz exceeds the chart axis. Bandwidth per published specification; not a measured response curve.

COVERAGE



APPLICATIONS

- Meeting rooms
- Multimedia rooms
- Small presentations
- Retail
- Hospitality