

SERENIX PROFESSIONAL AUDIO

SR-OFD-108

6.5" IP65 wall-mount speaker — transformer tapped, built for outdoor use.

A weatherproof commercial PA wall-mount speaker with transformer, rated IP65 for outdoor installation. The two-way system pairs a 6.5-inch woofer with a 1-inch tweeter through a dedicated crossover, and accepts 100 V, 70 V or 8-ohm connection. A 180-degree bracket allows the cabinet to be aimed precisely along walkways, courtyards and forecourts.

7.5–60 W	100 / 70 V	88 dB	IP65	70 Hz
TAPPINGS	AND 8 Ω	SENSITIVITY	WEATHER RATING	LOW CORNER



FEATURES

- 01

IP65 weatherproof

Sealed for outdoor installation in exposed walkways, courtyards and service areas.
- 02

Four power tapplings

7.5 / 15 / 30 / 60 W on 100 V or 70 V lines, or direct 8 Ω connection.
- 03

Two-way crossover

A dedicated crossover splits the 6.5-inch woofer and 1-inch tweeter for better clarity.
- 04

180° bracket


The supplied bracket swings through 180 degrees for accurate aiming after mounting.

SPECIFICATIONS

Description	6.5" weatherproof wall-mount speaker
Rated power output	7.5 / 15 / 30 / 60 W
Programme power	100 W
Line input	100 V, 70 V and 8 Ω
Crossover	Two-way
Frequency response	70 Hz–23 kHz
SPL (@ 1 W / 1 m)	92 ±3 dB
Sensitivity	88 dB @ 1 W / 1 m
IP rating	IP65 weatherproof
Dimensions	190 (W) × 201 (D) × 320 (H) mm
Material	ABS enclosure and metal grille
Mounting	180° wall-mount bracket
Weight	3.6 kg
Packing	520 × 320 × 420 mm, 2 pieces per carton

The source lists the grille finish as both white and black. All figures are nominal, per manufacturer data.

FREQUENCY RANGE



Published range extends to 23 kHz; chart axis ends at 20 kHz. Bandwidth per published specification; not a measured response curve.

HIGHLIGHTS

- IP65 rated for outdoor installation
- Four tapplings plus low-impedance operation
- Two-way crossover for improved clarity
- 180° aiming bracket supplied

APPLICATIONS

- Outdoor paging
- Schools
- Courtyards
- Forecourts
- Transport
- Background music