

SERENIX PROFESSIONAL AUDIO

SR-OFD-230PW-B

Bluetooth active wall pair — one powered main, one passive satellite.

A Bluetooth active wall-mounted speaker system consisting of one main active loudspeaker and one passive satellite. The main unit carries two channels of Class-D amplification and a Bluetooth receiver, with a Phoenix connector feeding the passive partner. Clear, articulate sound suits meeting rooms and multimedia rooms for small presentations; white and black finishes and an adjustable bracket are supplied.

20 W × 2 @ 8 Ω	Bluetooth RECEIVER	5" + 1" TWO-WAY	>70 dB S / N	4.8 kg PAIR WEIGHT
-------------------	-----------------------	--------------------	-----------------	-----------------------



FEATURES

- 01

Active plus passive

One powered main cabinet drives the passive satellite through a Phoenix connector.
- 02

Bluetooth and analogue

Built-in Bluetooth receiver alongside unbalanced RCA and balanced Phoenix inputs.
- 03

Mic and 100 V inputs

A 6.35 mm microphone jack and a 100 V signal input via RCA are available on the main unit.
- 04

Independent control


Separate volume for audio, Bluetooth, microphone and 100 V inputs, plus bass and treble.

SPECIFICATIONS

Rated power	20 W × 2 @ 8 Ω
Speaker units	Woofer 5" + tweeter 1"
Amplifier	2-channel digital stereo, Class D
Audio inputs	Balanced L&R via Phoenix; unbalanced L&R via RCA
Additional inputs	6.35 mm microphone jack; 100 V signal via RCA
Tone control	Bass and treble
Material	ABS enclosure, metal bracket and grille
Finish	White and black available
Frequency response	80 Hz–18 kHz at 1 W, ±3 dB
THD	<0.05 % at 1 kHz, 1/3 rated power
S / N	>70 dB
Protection	Over-temperature, overload
Power	AC 110 V; AC 220–240 V, 50–60 Hz
Dimensions	170 × 185 × 250 mm
Mounting	Adjustable U-shaped bracket
Net weight	4.8 kg (pair)

The source description also refers to this product as FWS-230B. All figures are nominal, per manufacturer data.

FREQUENCY RANGE



Bandwidth per published specification; not a measured response curve.

HIGHLIGHTS

- Main active unit drives one passive satellite
- Bluetooth receiver built in
- White and black finishes
- Adjustable mounting bracket supplied

APPLICATIONS

- Meeting rooms
- Multimedia rooms
- Small presentations
- Retail
- Hospitality