

SERENIX PROFESSIONAL AUDIO

SR-OCS-66

IP66-rated 6×6.5" outdoor aluminum column speaker — 100V / 70V line input with 120W / 60W power taps.

SR-OCS-66 is a high-power, six-driver outdoor column loudspeaker for commercial public address, covering both music and paging. Six 6.5-inch full-range waterproof drivers sit in an aluminum alloy enclosure finished in white, in a single slim 1.38m unit.

The speaker meets the IP66 weatherproof standard and connects through a cable tail with a waterproof gland, so wiring stays sealed outdoors. It accepts 100V or 70V constant-voltage lines with 120W / 60W power taps, and installs quickly using the supplied stainless-steel mounting bracket — well suited to factories, schools, offices, hotels, and airports.



IP66	98dB	120W	100V/70V	12.5kg
WEATHER RATING	SENSITIVITY	RATED POWER	LINE INPUT	NET WEIGHT

FEATURES

- 01

IP66 Weather Protection

Waterproof construction rated IP66, with a sealed cable tail and waterproof gland for outdoor wiring.
- 02

Aluminum Alloy Enclosure

Aluminum alloy cabinet and stainless-steel bracket in white for durable, all-weather installation.
- 03

100V / 70V Line Input

Built for constant-voltage PA lines, with 120W / 60W power taps to match room size and ambient noise.
- 04

Quick Installation

Supplied stainless-steel mounting bracket allows fast installation of the 1.38m unit.

SPECIFICATIONS

Model	SR-OCS-66
Configuration	6×6.5" full-range waterproof drivers, passive
Rated Power Output	120W / 60W (power taps)
Line Input	100V or 70V
Frequency Response	140Hz–15kHz
Sensitivity (1W/1m)	98dB
IP Rating	IP66
Connector	Speaker cable tail with waterproof gland
Dimensions (W×D×H)	1384 × 227 × 125mm
Material	Aluminum alloy enclosure, stainless-steel bracket, white
Mounting	Supplied stainless-steel bracket
Net Weight	12.5kg
Package Size	1430 × 250 × 160mm
Packed Weight	13.3kg

CONSTRUCTION

- Enclosure:** Aluminum alloy, white finish.
- Bracket:** Stainless steel, supplied for quick installation.
- Wiring:** Cable tail with waterproof gland for sealed outdoor connection.
- Weatherproofing:** IP66 rated.

APPLICATIONS

- Factories
- Schools
- Offices
- Hotels
- Airports
- Music & Paging

All figures are nominal, per manufacturer data.